

Titusville Morning Herald.

THE FIRST DAILY PAPER IN THE OIL REGIONS.

VOL. VIII. NO. 334.

TITUSVILLE, PA., SATURDAY, MAY 18, 1872.

WHOLE NO. 2134.

TUBING AND CASING.

CRESCENT

TUBE WORKS,

EVANS, DALZELL & CO.,

PITTSBURGH, PA.

Manufacturers of

LAP-WELD

Tubing & Casing,

Tested to 1,000 lbs. to the square inch.

Also, all sizes of

JELIN and GALLANARD

Wrought-Iron Pipe

From 1 to 10 inches in diameter.

B. W. STRATTNER, Agents

G. E. MITCHELL, on consignment.

4, Parshall House,

Spring St., Titusville.

Trade

Mark.

PASCAL IRON WORKS!

MORRIS,

TASKER & CO.,

Works No. 5th and Tasker Sts.,

Office 209 No. Third St.,

Philadelphia.

Manufacturers of

LAP-WELDED

OIL WELL

TUBE & CASING,

Wrought Iron

Welded Tubes,

in and Galvanized, from

1/2 inch to 8 inch Inside

diameter.

Lap-Welded Boiler Tubes,

from 1/2 to 1 inch, outside dia.

30 feet long, made of 1/2 to 1/4 inch.

Screening M.

and all assortments.

GAS AND STEAM PIPE.

TOOLS AND MATERIALS.

Cast and Malleable Iron Fittings,

BRASS AND IRON BODY VALVES

AND COUPLINGS.

of all sizes from 1/2 inch to 12 inch.

Gas Works, Lamp Posts, &c.

Our Oil Well Tubes are tested

before leaving our works, with

a pressure of 1,000 lbs. to the

square inch. Each length is

stamped near the screw with

our trade mark—the sockets

are no.

NATIONAL

TUBE WORKS CO.,

MANUFACTURERS OF

LAP-WELDED OIL WELL

Tubing & Casing,

We would call the particular attention of dealers

and producers to this make of Tubing and

Casing.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

and great strength to the

lasting throughout.

Each joint carefully inspected, reamed at each

end, and the tube bent by hydraulic

pressure of 1,000 pounds to the square inch before

being stamped with our trade mark.

Diamond "B."

50-12

are made perfectly straight, smooth and uniform,

